PRODUCT SPEC SHEET

R2-5MPFXBUL

# 5 MP IP IR Fixed Bullet

2560x1920 TRUE DAY/NIGHT

**The R2-5MPFXBUL is a 5MP (2560 x 1920) IP67 rated bullet camera constructed with a 2.8mm lens and provides HD Image quality.**
**OPTIONAL SERVICES***
**Integrate with Capture Cloud Service, powered by Eagle Eye***
**Connect with Capture Remote Monitoring Service (R2-B12SUBK)***
**Require monthly/annual subscriptions*

## FEATURES

- 2.8MM LENS
- IR DISTANCE: 30M/98FT
- SUPPORTS MICRO SD CARD, UP TO 256GB
- TRUE WDR
- ONVIF CONFORMANCE
- IP67
- POE/12VDC
- WARRANTY: 36 MONTHS

- PART #: R2-5MPFXBUL
- UPC: 840049305274

- LENGTH: 7.39"
- WIDTH: 2.52"
- HEIGHT: 2.52"
- WEIGHT: 1.32 LB

**FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.**

PRODUCT SPEC SHEET

R2-5MPFXBUL

# Caméra Ogivale Fixe IP IR 5 Mpx

JOUR/NUIT AUTHENTIQUE
2560 x 1920

**Le modèle R2-5MPFXBUL est un camera ogivale 5 Mpx (2560 x 1920) certifiée IP67 dotée d'un objectif de 2,8 mm et offrant une qualité d'image HD.**

**SERVICES EN OPTION***

**Intégrez-vous à Capture Cloud Service, optimisé par Eagle Eye.***

**Connexion aux services de surveillance à distance de Capture (R2-B12SUBK)***

**Nécessite un abonnement mensuel ou annuel*

## FEATURES

- OBJECTIF DE 2,8 MM
- DISTANCE (IR) : 30 M/98 PI
- PRISE EN CHARGE DES CARTES MICRO SD JUSQU'À 256 GO
- PLAGE DYNAMIQUE ÉTENDUE
- CONFORMITÉ ONVIF
- IP67
- POE/12 VCC
- GARANTIE : 36 MOIS

- PART #: R2-5MPFXBUL
- UPC: 840049305274

- LENGTH: 7.39"
- WIDTH: 2.52"
- HEIGHT: 2.52"
- WEIGHT: 1.32 LB

**FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.**

Capture advance

**TECHNICAL SPECIFICATION**

# R2-5MPFXBUL

| CAMERA | |
|---|---|
| IMAGE SENSOR | 1/2.8" PROGRESSIVE SCAN CMOS |
| EFFECTIVE PIXELS | 2560(H)×1920(V) |
| ELECTRONIC SHUTTER | AUTO/MANUAL, 1/5 ~ 1/20,000S |
| MIN. ILLUMINATION | COLOR: 0.03 LUX @ (F1.6, AGC ON) , B/W: 0 LUX @ (IR LED ON) |
| S/N RATIO | 55DB |
| DAY/NIGHT | AUTO(ICR) |
| WIDE DYNAMIC RANGE | TRUE WDR |
| IR RANGE | UP TO 30 M (98 FT) |
| IR ON/OFF CONTROL | AUTO/MANUAL |
| PAN/TILTROTATION RANGE | PAN: 0˚~ 360˚, TILT: 0˚~ 90˚, ROTATION: 0˚~ 360˚ |

| LENS | |
|---|---|
| LENS TYPE | FIXED FOCUS |
| IRIS | FIXED IRIS |
| FOCAL LENGTH | 2.8 MM (4 MM OPTIONAL) |
| F NUMBER | F2.0 |
| ANGLE OF VIEW | H: 93.4°, V: 69.1° |

| VIDEO | |
|---|---|
| MAX. RESOLUTION | 5MP (2560×1920) |
| STREAMING CAPABILITY | 3 STREAMS |
| STREAM/FRAME RATE | STREAM1: 2560×1920, 2592×1520, 1920×1080, 1280×720 @ 25/30FPS<br>STREAM2: D1, VGA, CIF @ 25/30FPS<br>STREAM3: VGA, CIF, QVGA @25/30FPS |
| BIT RATE CONTROL | CBR/VBR |
| BIT RATE | STREAM1: 200KBPS-12MBPS<br>STREAM2: 100KBPS-6MBPS<br>STREAM3: 100KBPS-3MBPS |
| IMAGE ENHANCEMENT | HLC / BLC / DEFOG / WDR |
| WHITE BALANCE | AUTO |
| GAIN CONTROL | AUTO/MANUAL |
| NOISE REDUCTION | 2D/3D DNR |
| AISLE MODE | SUPPORTED |
| SMART IR | SUPPORTED |
| MIRROR | SUPPORTED |
| REGION OF INTEREST | OFF/ON (8 ZONE, RECTANGLE) |
| MOTION DETECTION | SUPPORTED |
| PRIVACY MASKING | SUPPORTED |

| SMART FUNCTION | |
|---|---|
| SMART FUNCTION | SUPPORTS FACE, HUMAN, VEHICLE DETECTION |
| INTELLIGENT DETECTION | PERIMETER, SINGLE VIRTUAL FENCE, DOUBLE VIRTUAL FENCES, LOITER, PEOPLE COUNTING |

| AUDIO | |
|---|---|
| COMPRESSION | G.711, RAW_PCM |
| BIT RATE | 8KBPS, 16KPS, 64KBPS |

| NETWORK | |
|---|---|
| PROTOCOLS | IPV4/IPV6, 802.1X, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPOE, SMTP, DNS, UPNP, FTP, ARP, SNMP, TLS/SSL |
| INTEROPERABILITY | ONVIF, SDK, CGI |
| STREAMING METHOD | UNICAST |
| MAX. USER ACCESS | 10 USERS |
| WEB VIEWER | <IE11, CHROME, FIREFOX, MICROSOFT EDGE |
| MANAGEMENT SOFTWARE | CAPTURE ADV |

| INTERFACE | |
|---|---|
| ETHERNET | 1 ETHERNET (10/100 BASE-T) RJ-45 CONNECTOR |
| AUDIO | 1CH INPUT, 1CH OUTPUT |
| ALARM | 1CH INPUT, 1CH OUTPUT |
| RESET BUTTON | SUPPORTED |
| STORAGE | BUILT-IN MICRO SD SLOT, UP TO 256G |

| ELECTRICAL | |
|---|---|
| POWER SUPPLY | DC12V/POE (IEEE 802.3AF) |
| POWER CONSUMPTION | MAX 8.5 W |
| OPERATING TEMPERATURE | -40°C ~ 55°C (-40°F ~ 131°F ) |
| OPERATING HUMIDITY | LESS THAN 90% RH |
| INGRESS PROTECTION | IP67 |
| CERTIFICATIONS | CE/FCC |
| CASING | METAL |
| DIMENSIONS | 187.6 x 64 x 64MM (7.39" x 2.52" x 2.52") |
| NET WEIGHT | 0.6 KG (1.32 LB) |

**FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.**